

Sakkyndig Virksomhet
Enterprise of Competence
 Industriveien 12, 7652 Verdal, Norway

Certified by:



Approval no. SV 228



Report no.: Trygg test 010721E

Date: 01.07.2021

Page: 1 av 1

Technical Report in connection with Loadtesting/Inspection

Control type:		Project	:	
Initial control		Owner	:	SafeT AS
Periodic control		Type	:	Trygg
Erecting control		ID-no.	:	Prototype
Special Control		Serial no.	:	
Test / Overloadtest	X	Placed	:	

This Report includes the following Documents:

Description	Document no.	Pages
This document		
Total no. of pages enclosed		1

Comments:

It is performed a overload test of Trygg for shackle produced by SafeT AS

Trygg 3,25t is adapted for shackle WLL 3,25t and recommend roundsling up to 2tonn.
 This is tested and gives a minimum breaking load MBL 4tonn

Trygg 4,75t is adapted for shackle WLL 4,75t and recommend roundsling up to 3tonn
 This is tested and gives a minimum breaking load MBL 6tonn

Trygg 6,5t is adapted for shackle WLL 6,5t and recommend roundsling up to 5tonn
 This is tested and gives a minimum breaking load MBL 10tonn

Performed by:
 Eivind Horseng *Eivind Horseng*

Approved by:
 Jan Roar Nessemo *Jan Roar Nessemo*